



## PRODUCT HIGHLIGHTS

- Semi-professional three phase MIG welder
- Power indicator
- Thermal protection
- Digital display
- 12 heat setting for HGMIG250
- 20 heat setting for HGMIG300
- Stepless wire feed setting
- Spot timer adjustment
- Continuous spot welding
- Use 15kg or 20kgs wire spool

## NOTES

U1	Power supply
I1	Input current
P1	Input power
U0	No load voltage
I2	Output current range
X at I <sub>max</sub>	The duty cycle at rated current
Wire Dia	Wire Diameter

## TECHNICAL DATA

Model	DeltaMig-200	DeltaMig-250	DeltaMig-300
Input power (V)	400	400	400
Rated input current (A)	10	14	17.2
Rated input capacity (KVA)	6.6	9.2	11.5
Output open circuit voltage (V)	18-31	18-35	19-38
Welding current adjustment range (A)	40-200	40-250	56-00
Rated output (A)	35% at 200	35% at 250	35% at 300
Wire Dia (mm)	0.8-1.0	0.8-1.0	1.0-1.2
Weight (Kg)	72	75	86
Packing dimensions: L*W*H (mm)	800x375x700	800x375x700	830x395x770



MANUFACTURED UNDER  
**ISO 9001**  
 CERTIFIED  
 QUALITY  
 ASSURANCE SYSTEM

**Lion International U.K (M.E.) Limited**  
 Monomark House, 27 Old Gloucester Street, London WC1N 3XX, United Kingdom.  
 T: +44 20 74198760 F: +44 20 78319489 E: info@lionintweld.co.uk

**Lion International Middle East FZC**  
 P.O. Box 41654, W/H No. 1K-01/4, Hamriyah Free Zone, Sharjah, UAE.  
 T: +971 6 5260461 F: +971 6 5260561 E: info.me@lionintweld.co.uk