



PRODUCT HIGHLIGHTS

- Semi-professional IGBT inverter stick welder
- Power indicator
- Thermal protection
- Digital display
- Stepless current setting
- Hot start
- Anti-sticking
- Arc force
- Lift arc TIG
- Suitable for Rutile, Basic & Cellulosic electrodes.

TECHNICAL DATA

Model	InverArc 300E	InverArc 400E
Input power (V)	380	380
Rated input current (A)	25	29
Rated input capacity (KVA)	15	19
Output open circuit voltage (V)	68	68
Welding current adjustment range (A)	40-300	40-400
Rated output (A)	60% at 300	400
Weight (Kg)	19	19
Packing dimensions: L*W*H (mm)	655X325X455	655X325X455



MANUFACTURED UNDER
ISO 9001
CERTIFIED QUALITY
ASSURANCE SYSTEM

NOTES

U1	Power supply
I1	Input current
P1	Input power
U0	No load voltage
I2	Output current range
X at I _{max}	The duty cycle at rated current
Rod dia	Electrode diameter
Packing	Packing dimension

Lion International U.K (M.E.) Limited
Monomark House, 27 Old Gloucester Street, London WC1N 3XX, United Kingdom.
T: +44 20 74198760 F: +44 20 78319489 E: info@lionintweld.co.uk

Lion International Middle East FZC
P.O. Box 41654, W/H No. 1K-01/4, Hamriyah Free Zone, Sharjah, UAE.
T: +971 6 5260461 F: +971 6 5260561 E: info.me@lionintweld.co.uk