



### PRODUCT HIGHLIGHTS

- IGBT inverter three phase separate wire feeder MIG/STICK welder
- Power indicator
- Thermal protection
- Digital display
- Stepless heat and wire speed setting
- Four roller
- Manual wire feeding
- Burn back
- Gas check
- Crater A/V adjustment □ Available for 15kgs or 20kgs wire spool

### NOTES

U1	Power supply
I1	Input current
P1	Input power
U0	No load voltage
I2	Output current range
X at I <sub>max</sub>	The duty cycle at rated current
Wire Dia	Wire Diameter

### TECHNICAL DATA

Model	InverMig-350	InverMig-500	InverMig-630
Input power (V)	380	380	380
Rated input current (A)	25.5	41.8	54.4
Rated input capacity (KVA)	16.8	27.5	35.8
Output open circuit voltage (V)	60	68	91
Welding current adjustment range (A)	40-350	50-500	60-630
Rated output (A)	60% at 350	60% at 500	60% at 630
Wire Dia (mm)	0.8-1.2	0.8-1.6	1.0-2.0
Weight (Kg)	45	50	55
Packing dimensions: L*W*H (mm)	1035x430x955	1035x430x955	1035x430x955



MANUFACTURED UNDER  
**ISO 9001**  
CERTIFIED  
QUALITY  
ASSURANCE SYSTEM

**Lion International U.K (M.E.) Limited**

Monomark House, 27 Old Gloucester Street, London WC1N 3XX, United Kingdom.  
T: +44 20 74198760 F: +44 20 78319489 E: info@lionintweld.co.uk

**Lion International Middle East FZC**

P.O. Box 41654, W/H No. 1K-01/4, Hamriyah Free Zone, Sharjah, UAE.  
T: +971 6 5260461 F: +971 6 5260561 E: info.me@lionintweld.co.uk