

## Conventional Rotators



Askaynak conventional rotator systems can be used in applications where diameter difference is not too much. Rotator systems consist of 1 unit motorized and 1 unit idler rotator assemblies. Motorized four wheel rotator assembly provides rotation without slippage.

### Standard Features

- Synchronized operation with column-booms
- Durable external painting resistance against scratches and damages
- PU coated wheels

### Optional Features

- Wireless remote control
- Motorized or manual carriage
- Structure with high base for special applications

MODEL	AS KR 5T	AS KR 10 T	AS KR 20 T	AS KR 40T
FEATURE				
Maximum Capacity	5000 Kg	10000 Kg	20000 Kg	40000 Kg
Minimum Rotating Diameter	400 mm	500 mm	750 mm	750 mm
Maximum Rotating Diameter	3000 mm	4000 mm	4500 mm	5000 mm
Length x Width x Height	2200 x 500 x 450 mm	3200 x 900 x 700 mm	3600 x 1200 x 800 mm	3050 x 850 x 1035 mm
Wheel Diameter and Width	Ø250 x 60	Ø450 x 70 – 2 Adet	Ø500 x 70 – 2 Adet	Ø500 x 100 – 3 Adet
Engine Power	0.25 Kw x 2	0.37 Kw x 2	0.37 Kw x 2	0.37 kw x 2

## Conventional Rotators

